

ROKKER Series Tweeter Kit

For 1998-2013 Harley® Dresser

Part#HTWT-1025-CRT

Installation & Operation Instructions

Product Description

This exciting new J&M ROKKER series tweeter kit has been design specifically for use on the 1998-2013 Harley® Ultra-Classic (BatWing) or RoadGlide style fairing.

These are 25mm diameter high-output dome tweeters designed to bring extra high-frequency definition to your Harley Bagger audio system.

Tweeters are spec'd at 2 ohms nominal impedance, and will work with any radio or amplifier designed to operate at a 2, 4, 6 or 8-ohm load.

Rated at 300w peak power (150w RMS), 3,000 - 21khz frequency range, & 94db sensitivity @ 1w, 1m, these tweeters can easily replace

two of the stock Harley gauges on the inside fairing panel.

These new 'J&M ROKKER series tweeters will connect direct to the midrange output jack on the back of the 'J&M ROKKER series speaker crossover network, OR to the front speaker spade connections inside

the fairing, using the custom made plug-n-play wiring harnesses included.

This kit includes 2 tweeters, alternate connection wire assemblies, along with all necessary mounting hardware & complete installation instructions.

Installation Instructions

- 1. Remove the outer fairing shell.
- 2. Remove both lower gauges next to the radio, retain the gauge cups and nuts to be used on the tweeters.
- 3. Install the tweeter using the previously removed gauge cups and nuts.

4a. Connect the tweeters to the speaker wires between the radio head unit and the main fairing speakers, or between the radio head unit and booster amplifier inputs, with the Y-wire harness plugs provided.

OF

4b. Connect the tweeters using the attached white two pin connectors, to the midrange crossover plug on the back of the J&M ROKKER or ROKKER XT speakers.

WARRANTY AND REPAIR INFORMATION

TWO YEAR LIMITED WARRANTY In order to facilitate the servicing of this warranty, the Warranty Registration Form should be filled out and returned within 10 days of the date of purchase. However, return of the Warranty Registration Form is not a precondition of this warranty, and this Warranty will be observed by **J&M CORPORATION** whether or not the Warranty Registration Form is returned, on the condition that other satisfactory evidence of the date of the original purchase is provided to **J&M CORPORATION**.

WHO PROVIDES THE WARRANTY? This warranty is provided by J&M CORPORATION.

WHO IS PROTECTED? This warranty is extended only to the original owner of this J&M CORPORATION product and may not be transferred or assigned.

WHAT IS COVERED AND HOW LONG? This warranty covers all defects in material or workmanship of our product for a period of 2 years from date of original retail purchase. At its option, J&M CORPORATION will repair or replace any defective part(s) or equipment.

The provisions of the warranty shall not apply to any unit which has been subjected to misuse, neglect, incorrect mechanical or electrical installation, unauthorized modifications, accident, nor to units which have been repaired or altered outside of our factory.

PROCEDURE FOR OBTAINING PERFORMANCE OF WARRANTY In the event that the product does not conform to this warranty, the product should be shipped prepaid to the J&M CORPORATION service facility. Transportation charges, insurance fees, and labor costs for shipment, removal, or reinstallation of our product are not covered by this warranty. Loss or damage in shipment is the sole responsibility of the freight carrier.

FOR YOUR INFORMATION Repair as provided under this warranty is the exclusive remedy of the consumer. **J&M CORPORATION** shall not be liable for any incidental or consequential damages or for breach of any express or implied warranty on this product. Except to the extent prohibited by applicable law, any implied warranty of merchantability or fitness for a particular purpose on this product is limited in duration to the duration of the warranty. Some states do not allow the exclusion or limitation of incidental or consequential damages, or allow limitations on how long an implied warranty lasts, so the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights which vary from state to state.

J&M CORPORATION reserves the right to make changes in design and to make improvements in its products without the obligation to incorporate the changes or improvements in any of its previously manufactured products.

J&M CORPORATION has not authorized anyone to make representations or warranties other than the warranty contained herein. The above warranty is effective for all products manufactured after 10/01/86.

NON-WARRANTY REPAIR RATES J&M CORPORATION reserves the right to change the labor repair rates without prior notice. At the time of this printing the out-of- warranty repair is \$40 per hour for labor only. However, the customer is advised to verify the

current rate when he/she calls customer service to obtain the return authorization number.

FACTORY SERVICE ADDRESS J&M Corporation, 1415 S. Cherry Avenue, Tucson, Arizona, 85713, U.S.A. Tel: 1-800-358-0881 audio@jmcorp.com www.jmcorp.com CUSTOMER SERVICE NUMBER 1-800-358-0881

Thank you for the confidence you have shown in J&M Corporation by purchasing one of our innovative products.

If you have any question or comments about this product, you may contact us at USA 1-520-624-7000 Monday thru Friday, 8:00AM thru 5:00PM Mountain Standard Time.



1415 S. Cherry Avenue
Tucson, AZ 85713 U.S.A.
Tel (800) 358-0881
Website: http://www.jmcorp.com

E-mail: audio@jmcorp.com

WARRANTY REGISTRATION FORM Please fill out this card completely and mail it immediately after purchase. Please be sure that your zip code and serial number (if applicable) are legible. This will help us to serve you better.

(PLEASE PRINT)					
Name					
Address					
City		State	_ Zip		
Motorcycle O Other O	E-mail				
Make	_ Model		Year		
Product part number					Mail to:
Serial number (if applicable)				CORPORATION	J&M Corporation 1415 S. Cherry Avenue
Date of purchase					Tucson, AZ 85713 U.S.A.
Name of dealer it was purchased from					